

Polyester Slings Flat & Round



TECHNICAL PARAMETERS

Capacity	Type	Colour	Rated Working Load (Tons)				Width (mm)
			Vertical	Basket	Chocker	Angle 90°	
1	Flat		1	2	0.8	1.4	25
1	Round		1	2	0.8	1.4	
2	Flat		2	4	1.6	2.8	50
2	Round		2	4	1.6	2.8	
3	Flat		3	6	2.4	4.2	75
3	Round		3	6	2.4	4.2	
4	Flat		4	8	3.2	5.6	100
4	Round		4	8	3.2	5.6	
5	Flat		5	10	4.0	7.0	125
5	Round		5	10	4.0	7.0	
6	Flat		6	12	4.8	8.4	150
6	Round		6	12	4.8	8.4	
8	Flat		8	16	6.4	11.2	200
8	Round		8	16	6.4	11.2	
10	Flat		10	20	8.0	14.0	250
10	Round		10	20	8.0	14.0	
12	Flat		12	24	9.6	16.8	300
12	Round		12	24	9.6	16.8	
16	Flat		16	32	12.8	22.4	300
16	Round		16	32	12.8	22.4	
20	Flat		20	40	16.0	28.0	300
20	Round		20	40	16.0	28.0	

* Extra Lifts & Higher sizes are available on request

- Much lighter than metal slings, easy to handle.
- High performance fibre, high safety.
- Non corrosive, non conductive, non sparking.
- Very simple, easy and safe to operate.
- Prevention of slip and damage on the surface of finished goods.
- Wide surface hence less pressure at the points of contact of the lifting object.